

Klemmgehäuse | STB

Stahlblech
 RAL7035
 IP66
 inkl. Montageplatte



Artikelnummer	H	B	T
STB 1515 08	150	150	80
STB 1530 08	150	300	80
STB 2020 08	200	200	80
STB 2030 08	200	300	80
STB 2040 08	200	400	80
STB 3030 08	300	300	80
STB 1515 12	150	150	120
STB 1530 12	150	300	120
STB 2020 12	200	200	120
STB 2030 12	200	300	120
STB 2040 12	200	400	120
STB 2050 12	200	500	120
STB 2060 12	200	600	120
STB 2080 12	200	800	120
STB 3030 12	300	300	120
STB 3040 12	300	400	120
STB 3050 12	300	500	120
STB 3060 12	300	600	120
STB 4040 12	400	400	120
STB 4060 12	400	600	120
STB 4080 12	400	800	120

Klemmgehäuse | SSTB

Edelstahl
 IP66
 inkl. Montageplatte



Artikelnummer	H	B	T
SSTB 1515 08	150	150	80
SSTB 1530 08	150	300	80
SSTB 2020 08	200	200	80
SSTB 2030 08	200	300	80
SSTB 2040 08	200	400	80
SSTB 3030 08	300	300	80
SSTB 1515 12	150	150	120
SSTB 1530 12	150	300	120
SSTB 2020 12	200	200	120
SSTB 2030 12	200	300	120
SSTB 2040 12	200	400	120
SSTB 2050 12	200	500	120
SSTB 2060 12	200	600	120
SSTB 2080 12	200	800	120
SSTB 3030 12	300	300	120
SSTB 3040 12	300	400	120
SSTB 3050 12	300	500	120
SSTB 3060 12	300	600	120
SSTB 4040 12	400	400	120
SSTB 4060 12	400	600	120
SSTB 4080 12	400	800	120

Pult-Systeme | MPC, MPKS

Stahlblech
 RAL7035
 IP66 = eintürig
 IP55 = doppeltürig ab 1200 mm Breite
 inkl. Montageplatte
 Bestellung in Edelstahl:
 MPKS anstatt MPC in Artikelnummer



Artikelnummer	H	B	T
Pultaufsatz			
MPC 061	500	600	494
MPC 081	500	800	494
MPC 101	500	1000	494
MPC 121	500	1200	494
MPC 161	500	1600	494
Pultmittelteil			
MPC 062	250	600	985
MPC 082	250	800	985
MPC 102	250	1000	985
MPC 122	250	1200	985
MPC 162	250	1600	985
Pultunterteil			
MPC 063	700	600	500
MPC 083	700	800	500
MPC 103	700	1000	500
MPC 123	700	1200	500
MPC 163	700	1600	500

Pulte | MPG, MPGS

Stahlblech
 RAL7035
 P66 = eintürig
 IP55 = doppeltürig ab 1200 mm Breite
 inkl. Montageplatte
 Bestellung in Edelstahl:
 MPGS anstatt MPG in Artikelnummer



Artikelnummer	H	B	T
MPG 06	985	600	400
MPG 08	985	800	400
MPG 10	985	1000	400
MPG 12	985	1200	400
MPG 16	985	1600	400